

Marking and Labeling Systems – Component

COMPANY
MH25987
Guangdong Tianyue Printing Tech. Co., Ltd.

601 TOWER2

TIANFULAI INTERNATIONAL INDUSTRIAL CITY

RONGGUI SHUNDE

Foshan, Guangdong 528305 China

Model No.	Application Surface	Min Temp (°C)	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
-----------	---------------------	---------------	---------------	------------	-------------	-----------------------

Pressure-sensitive printed labels Description – printed white acrylic facestock with adhesive which is protected by a release liner

TY100-210

	Acrylic paint	-40	175	X	X	-
	Alodined aluminum	-40	175	X	X	-
	Aluminum	-40	175	X	X	-
	Anodized aluminum	-40	175	X	X	-
	Epoxy/Polyester powder paint	-40	175	X	X	-
	Galvanized steel	-40	175	X	X	-
	Polyester paint	-40	175	X	X	-
	Polyester powder paint	-40	175	X	X	-
	Porcelain	-40	175	X	X	-
	Silicone paint	-40	175	X	X	-
	Stainless steel	-40	175	X	X	-
	Nylon – Polyamide	-	100	X	-	-
	Phenolic – Phenol Formaldehyde	-40	100	X	X	-
	Polycarbonate	-40	100	X	X	-
	Acrylonitrile butadiene styrene	-40	80	X	X	-
	Polyphenylene oxide/ether	-40	80	X	X	-
	Polypropylene	-	80	X	-	-
	Polystyrene	-40	80	X	X	-

Pressure-sensitive printed labels

TY867-150

	Acrylic paint	-	150	X	-	-
--	---------------	---	-----	---	---	---

	Alkyd paint	-	150	X	-	-
	Aluminum	-40	150	X	-	-
	Epoxy paint	-	150	X	-	-
	Epoxy powder paint	-40	150	X	-	-
	Galvanized steel	-	150	X	-	-
	Polyester paint	-	150	X	-	-
	Porcelain	-	150	X	-	-
	Stainless steel	-	150	X	-	-
	Nylon - Polyamide	-40	100	X	-	-
	Phenolic - Phenol Formaldehyde	-	100	X	-	-
	Polycarbonate	-40	100	X	-	-
	Acrylic	-40	80	X	-	-
	Melamine	-40	80	X	-	-
	Polyethylene	-40	80	X	-	-
	Polyphenylene oxide/ether	-	80	X	-	-
	Polypropylene	-40	80	X	-	-
	Polystyrene	-	80	X	-	-
	Unsaturated polyester - thermoset	-40	80	X	-	-
	Acrylonitrile butadiene styrene	-	60	X	-	-

TY868-125

	Alkyd paint	-	125	X	-	-
	Aluminum	-	125	X	-	-
	Stainless steel	-	125	X	-	-
	Polycarbonate	-	80	X	-	-
	Acrylonitrile butadiene styrene	-	60	X	-	-

TY868-150

	Acrylic paint	-	150	X	-	-
	Alkyd paint	-	150	X	-	-
	Aluminum	-40	150	X	-	-
	Epoxy paint	-	150	X	-	-
	Epoxy powder paint	-40	150	X	-	-
	Galvanized steel	-	150	X	-	-
	Polyester paint	-	150	X	-	-
	Porcelain	-	150	X	-	-
	Stainless steel	-	150	X	-	-
	Nylon - Polyamide	-40	100	X	-	-
	Phenolic - Phenol Formaldehyde	-	100	X	-	-

	Polycarbonate	-40	100	X	-	-
	Acrylic	-40	80	X	-	-
	Melamine	-40	80	X	-	-
	Polyethylene	-40	80	X	-	-
	Polyphenylene oxide/ether	-	80	X	-	-
	Polypropylene	-40	80	X	-	-
	Polystyrene	-	80	X	-	-
	Unsaturated polyester - thermoset	-40	80	X	-	-
	Acrylonitrile butadiene styrene	-	60	X	-	-

TY869-150

	Acrylic paint	-40	150	X	X	-
	Acrylic powder paint	-40	150	X	X	-
	Aluminum	-40	150	X	X	-
	Epoxy paint	-40	150	X	X	-
	Epoxy powder paint	-40	150	X	X	-
	Galvanized steel	-40	150	X	X	-
	Polyester powder paint	-40	150	X	X	-
	Porcelain	-40	150	X	X	-
	Stainless steel	-40	150	X	X	-
	Alkyd paint	-40	100	X	X	-
	Melamine	-40	100	X	-	-
	Nylon - Polyamide	-40	100	X	-	-
	Phenolic - Phenol Formaldehyde	-40	100	X	-	-
	Polyester paint	-40	100	X	X	-
	Unsaturated polyester - thermoset	-40	100	X	-	-
	Acrylonitrile butadiene styrene	-40	80	X	-	-
	Polycarbonate	-40	80	X	X	-
	Polyphenylene oxide/ether	-40	80	X	-	-
	Polystyrene	-40	80	X	-	-
	Alkyd painted plastic	-40	60	X	-	-
	Polyethylene	-	60	X	-	-

TY968-125

	Alkyd paint	-40	125	X	X	-
	Aluminum	-40	125	X	X	-
	Stainless steel	-40	125	X	X	-
	Polycarbonate	-40	80	X	X	-
	Acrylonitrile butadiene styrene	-40	60	X	X	-

TY968-125B

	Alkyd paint	-40	125	X	X	-
	Aluminum	-40	125	X	X	-
	Stainless steel	-40	125	X	X	-
	Unsaturated polyester - thermoset	-40	125	X	X	-
	Acrylonitrile butadiene styrene	-40	80	X	X	-
	Polycarbonate	-40	80	X	X	-

TY969-125

	Alkyd paint	-40	125	X	-	-
	Aluminum	-40	125	X	-	-
	Stainless steel	-40	125	X	-	-
	Polycarbonate	-40	80	X	-	-
	Acrylonitrile butadiene styrene	-40	60	X	-	-

TY969-125B

	Alkyd paint	-20	125	X	-	-
	Aluminum	-20	125	X	-	-
	Stainless steel	-20	125	X	-	-
	Polycarbonate	-20	80	X	-	-
	Acrylonitrile butadiene styrene	-20	60	X	-	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

Marking: Company name and model designation.

Last Updated on 2021-10-19

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."